



(0,80 mm) .0315"

ERF8 SERIES



ERF8-020-05.0-S-DV-TR

ERF8-060-05.0-L-DV-TR

ERF8-040-05.0-S-DV-TR

RUGGED HIGH SPEED SOCKET



SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?ERF8

Insulator Material: Black LCP
Contact Material: BeCu
Plating: Au or Sn over 50µ" (1,27 µm) Ni
Current Rating: 2.2 A per pin (1 pin powered per row)
Operating Temp Range: -55°C to + 125°C
Voltage Rating: 200 VAC max
RoHS Compliant: Yes


Processing:
Lead-Free Solderable: Yes
SMT Lead Coplanarity:
 (0,10 mm) .004" max (005-030)
 (0,12 mm) .005" max (040-060)
 (0,15 mm) .006" max (070-075)

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



FILE NO. E111594




Board Mates:
ERM8

Cable Mates:
ERCD, ERDP



Robust Edge Rate™ contact improves "Zippered" unmating

10 to 150 I/Os



25+

Gbps

ERM8/ERF8 7 mm Stack Height	Rated @ 3dB Insertion Loss	
	with PCB effects*	w/o PCB effects**
Single-Ended Signaling	10.5 GHz / 21 Gbps	12 GHz / 24 Gbps
Differential Pair Signaling	9.5 GHz / 19 Gbps	15.5 GHz / 31 Gbps

*Performance data includes effects of a non-optimized PCB.

**Test board losses de-embedded from performance data.

Performance data for other stack heights and complete test data available at www.samtec.com?ERF8 or contact sig@samtec.com



(1,50 mm)
.059"
NOMINAL
WIPE

ERF8 LEAD STYLE	MATED HEIGHT*			
	ERM8 LEAD STYLE			
	-02.0	-05.0	-08.0	-09.0
-05.0	(7,00) .276	(10,00) .394	(13,00) .512	(14,00) .551
-07.0	(9,00) .354	(12,00) .472	(15,00) .591	(16,00) .629

*Processing conditions will affect mated height.

ERF8	NO. OF POSITIONS PER ROW	LEAD STYLE	PLATING OPTION	DV	OTHER OPTION	TR
	-005, -010, 011, -013, -020, -025, -030, -035 -040, -049, -050, -060, -070, -075, -100	Specify LEAD STYLE from chart	-L = 10µ" (0,25 µm) Gold on contact, Matte Tin on tail -S = 30µ" (0,76 µm) Gold on contact, Matte Tin on tail -EGP = Extended Guide Post (Lead Style -07.0 only) (N/A with -L & -EGPS option) -EGPS = Extended Guide Post Shield (Lead Style -07.0 only) (N/A with -L & -EGP option) (-010, -020, -025, -030 only) -K = (6,00 mm) .236" DIA Polyimide Film Pick & Place Pad	-TR = Tape & Reel Packaging		

SERIES
ERF8-DV
ERF8-DV
ERF8-DV
ERF8-DV
ERF8-DV
ERF8-DV
ERF8-DV
ERF8-DV

No. of Positions x
(0,80) .0315 + (6,00) .236

-L & -EGP = No. of Positions x
(0,80) .0315 + (7,50) .295

-EGPS = No. of Positions x
(0,80) .0315 + (10,00) .394

(3,35) .132 (5,60) .220

01

Diagram of the ERF8-DV component showing dimensions and lead styles. The component is a rectangular package with a grid of pins. Dimensions are given in inches and millimeters. The lead style is specified as -L (10µm) or -S (30µm). The diagram shows the component with a lead style of -L (10µm) and a lead style of -S (30µm). The dimensions are: (3,35) .132, (5,60) .220, and 01.

LEAD STYLE	A
-05.0	(5,10) .200
-07.0	(7,00) .276

(7,25) .285


Diagram of the ERF8-DV component showing dimensions and lead styles. The component is a rectangular package with a grid of pins. Dimensions are given in inches and millimeters. The lead style is specified as -L (10µm) or -S (30µm). The diagram shows the component with a lead style of -L (10µm) and a lead style of -S (30µm). The dimensions are: (7,25) .285.

-EGP

LEAD STYLE	A
-05.0	(5,10) .200
-07.0	(7,00) .276

APPLICATIONS

STANDARD	POS.	PART NOS.	SERIES
NEXUS5001™.org POWER.org™	10	ASP-148421-01	ERF8-DV
	11	ASP-137969-01	ERF8-DV
	17	ASP-137973-01	ERF8-DV
ARM/HSSTP	20	ASP-130367-01	ERF8-DV
	23	ASP-130368-01	ERF8-DV
NEXUS5001™.org POWER.org™	25	ASP-148422-01	ERF8-DV
	35	ASP-135029-01	ERF8-DV
	40	ASP-148424-01	ERF8-DV



ALSO AVAILABLE (MOQ Required)

- Mezzanine stack heights
- Contact Samtec.

Note: Some lengths, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: +1-800-SAMTEC-9 or +1-812-944-6733 SAMTEC NORTHERN CALIFORNIA • Tel: +1-408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: +1-800-726-8329
 SAMTEC SOUTH AMERICA • Tel: +55 31 3786 3227 SAMTEC UNITED KINGDOM • Tel: +44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
 SAMTEC FRANCE • Tel: +33 1 60 95 06 60 SAMTEC ITALY • Tel: +39 039 6890337 SAMTEC NORDIC/BALTIC • Tel: +46 8 4477280 SAMTEC BENELUX • Tel: +44 01236 739292
 SAMTEC ISRAEL • Tel: +972 3 7526600 SAMTEC INDIA • Tel: +91 80 3272 1612 SAMTEC ANZ • Tel: +613 9580 0683 SAMTEC SINGAPORE • Tel: +65 6745 5955 SAMTEC JAPAN • Tel: +81 45 475 1385
 SAMTEC SHANGHAI • Tel: +86 21 6083 3766 SAMTEC SHENZHEN • Tel: +86 755 83776780 SAMTEC TAIWAN • Tel: +886 2 2735 6109 SAMTEC HONG KONG • Tel: +852 26904658 SAMTEC KOREA • Tel: +82 31 717 5685