

MICRO SWITCH

FREEPORT ILLINOIS, U.S.A
A DIVISION OF HONEYWELL

FED. MFG. CODE 91929

ACTUATOR-SWITCH

CATALOG LISTING

JS-150

JS-150

M

DRAWING
NUMBER

ISSUE

4

8/4

REVISIONS

A	MADE ETS	15 MAY 70
B	PR-2722	19 JUN 72
C	C079303	7 MAR 95

REPLACES

RELEASE NO. PR-2722

CHECK

1/1 AUG 69

CHECK

1/1 AUG 69

CHECK

1/1 AUG 69




CHECK

1/1 AUG 69

2-56 UNC CORROSION RESISTANT STEEL
HEX NUT (2) $\triangle 1$

CORROSION RESISTANT STEEL
LOCKWASHER (2) $\triangle 1$

2-56 UNC X .500 REF CORROSION RESISTANT
STEEL ROUND HEAD MACHINE SCREW (2) $\triangle 1$



NOTE -



- FURNISHED UNASSEMBLED
CHARACTERISTICS WITH IHM19 (MS27216-1)
BASIC SWITCH INSTALLED

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS

$\triangle 2$

OPERATING FORCE	— — — 14 OZ MAX
RELEASE FORCE	— — — 2 OZ MIN
PRETRAVEL	— — — .078 MAX
DIFFERENTIAL TRAVEL	— — — .020 MAX
OVERTRAVEL	— — — .014 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT

SCALE FULL

DO NOT SCALE PRINT

UNLESS OTHERWISE
NOTED

DIMENSIONS ARE IN INCHES

TOLERANCES ARE:

ONE PLACE	(.0)	± .030
TWO PLACE	(.00)	± .015
THREE PLACE	(.000)	± .005
ANGLES		± 2°

WEIGHT

FO-50378-1A

DRAWN

19 AUG 69

1/1 AUG 69