



MLC

MLC - ideal for general-purpose settings and as supplementary task lighting in patient rooms. A 9.5 in. (241 mm) diameter shade with inner reflector and 6-ring louver eliinates glare and protects against bulb breakage. Heavy duty, 20-gauge, CRS K-arm with 0.5 in. (13 mm) square tubing and internal tempered steel springs assures proper balance and ease of movement while providing optimal durability.



- 9.5 in. (241 mm) diameter shade with inner reflector
- 6-ring louver
- Heavy-duty, 20-gauge, CRS K-arm
- UL/CUL Listed
- Mounting options sold separately
- Color: Light Grey





CODES

MLC100S - 18IN. CORD LENGTH

Article Number	Light Source 22W	Weight	Arm Length	Mount	Ct	n. Colors
14251LG	Fluorescent and 60W Incandescent	8.8	45.0/1143	3 Wall mount solo	l separately 1	н
14251WT	22W Fluorescent and 60W Incandescent	8.8	45.0/1143	3 Wall mount solo	l separately 1	

MLC145 - 5FT. CORD LENGTH ***LIMITED QUANTITIES AVAILABLE***

Article Number	Light Source	Weight	Arm Length	Mount	Ctn. Colors
14255LG	22W Fluorescent and 60W Incandescent	8.8	45.0/1143	B Edge/Floor mount sold separately :	
14255WT	22W Fluorescent and 60W Incandescent	8.8	45.0/1143	B Edge/Floor mount sold separately :	

MLC150S - 18IN. CORD LENGTH

Article Number	Light Source	Weight	Arm Length	Mount	Ctn. Colors
14261LG	22W Fluorescent and 60W Incandescent	8.8	50.0/1270	Wall mount sold separately	1
14261WT	22W Fluorescent and 60W Incandescent	8.8	50.0/1270	Wall mount sold separately	1 🔲

ACCESSORIES DESIGNATION

34" Floor Stand (for use with model 14255LG only)	50036
Wall Bracket	50003
Edge Clamp	60001
Louver/6-Ring	31628
MLC Surface Mount	50034
Double Gang Box Mount	50024

COLORS DESIGNATION