

STANDARD SILVER CONTACTS				GOLD PLATED CONTACTS							
ELECTRICAL RATING				ELECTRICAL RATING		ENVIRONMENTAL		APPROVALS			
AC		DC		$I_{th} = 10A$		IP66 NEMA 1, 4, 12, 13 TEMP RANGE : -25°C TO 85°C -13°F TO 185°F STORAGE : -40°C TO 85°C -40°F TO 185°F SHOCK : 50G PER IEC 68-2-27 VIBRATION : 10G PER IEC 68-2-6		 IEC 947-5-1 EN50047			
A300 Ue	AC15 Ie	O300 Ue	DC13 Ie								
VOLTS 120 240	AMPS 6 3	VOLTS 125 250	AMPS 0.50 0.27								
1V 10μA MIN.		50V 100mA MAX.									
THE COPYRIGHT OF THIS DRAWING IS THE PROPERTY OF HONEYWELL LTD. THE DRAWING IS SUPPLIED IN CONFIDENCE AND MUST NOT BE USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SUPPLIED.				THIRD ANGLE PROJECTION		SCALE 1:1		DIMENSIONS ARE IN MM/INCHES.		MODIFY ON CAD SYSTEM ONLY	

(906)

1/2" NPT X 1/4 CONDUIT
THREAD ADAPTER

A



4

HEAD ORIENTATION WITH
ACTUATOR ON OPPOSITE SIDE
FROM STANDARD.

Q07

CONNECTOR ,5 PIN MICRO.
ONLY AVAILABLE WITH CONDUIT
THREAD TYPE 'B'.

NOTE:
FOR CONNECTION DIAGRAMS AND ADDITIONAL
ELECTRICAL, ENVIRONMENTAL & DIMENSIONAL
INFORMATION SEE DRAWING GL-4922.