


STANDARD SILVER CONTACTS		GOLD PLATED CONTACTS			
ELECTRICAL RATING		ELECTRICAL RATING		ENVIRONMENTAL	
AC A300 AC15 U_e I_e VOLTS AMPS 120 6 240 3		DC O300 DC13 U_e I_e VOLTS AMPS 125 0.55 250 0.27		I_{th} = 10A 1V 10μA MIN. 50V 100mA MAX.	
				IP66 NEMA 1, 4, 12, 13 TEMP RANGE : -25°C TO 85°C -13°F TO 185°F STORAGE : -40°C TO 85°C -40°F TO 185°F SHOCK : 50G PER IEC 68-2-27 VIBRATION : 10G PER IEC 68-2-6	
				UL SP IEC 947-5-1 EN50047	
THE COPYRIGHT OF THIS DRAWING IS THE PROPERTY OF HONEYWELL LTD. THE DRAWING IS SUPPLIED IN CONFIDENCE AND MUST NOT BE USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT IS SUPPLIED.		THIRD ANGLE PROJECTION 		SCALE 1:1 DIMENSIONS ARE IN MM/INCHES.	
				MODIFY ON CAD SYSTEM ONLY	

