


Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272
Powerex, Europe, S.A. 428 Avenue G. Durand, BP107, 72003 Le Mans, France (43) 41.14.14


Fast Recovery Rectifier
220 Amperes Average
1600 Volts



CASE NUMBER R60		STRIKE DISTANCE : .48 INCH / 12.2 MM MIN.									
NOMINAL DIMENSIONS		CREEPAGE DISTANCE : .48 INCH / 12.2 MM MIN.									
SYM.		A	B	C	D	E	F	G	H	J	K
INCHES		.81	.55	1.50	2.30	1.05	5.44	.73	.343	-----	-----
MM		20.6	14.0	38.1	58.4	26.7	138.2	18.5	8.71	-----	-----

ALL DIMENSIONS ARE REFERENCE

R602_22/R603_22 (Outline Drawing)



R602_22/R603_22
Fast Recovery Rectifier
220 Amperes Average, 1600 Volts

Features:

- ☐ Fast Recovery Times
- ☐ Soft Recovery Characteristics
- ☐ Standard and Reverse Polarities
- ☐ Flag Lead and Stud Top Terminals Available
- ☐ High Surge Current Ratings
- ☐ High Rated Blocking Voltages
- ☐ Special Electrical Selection for Parallel and Series Operation
- ☐ Glazed Ceramic Seal Gives High Voltage Creepage and Strike Paths
- ☐ Special Selection of Recovery Characteristics Available

Applications:

- ☐ Inverters
- ☐ Choppers
- ☐ Transmitters
- ☐ Free Wheeling Diode

Ordering Information:

Select the complete part number you desire from the following table:

Type	Voltage		Current		Recovery Time		Leads	
	V _{RRM} (Volts)	Code	I _{F(av)} (A)	Code	t _{rr} (nsec)	Code	Case	Code
R602 (Standard Polarity)	400	04	220	22	500	PS	DO-9	YA
	600	06						
	800	08						
	1000	10						
R603 (Reverse Polarity)	1200	12						
	1400	14						
	1600	16						

Example: Type R602 rated at 220A average with V_{RRM} = 1600V, Recovery Time = 500nsec, order as:

Type				Voltage		Current		Time	Leads	
R	6	0	2	1	6	2	2	PS	Y	A

Powerex, Inc., 200 Hillis Street, Youngwood, Pennsylvania 15697-1800 (412) 925-7272
Powerex, Europe, S.A. 428 Avenue G. Durand, BP107, 72003 Le Mans, France (43) 41.14.14

R602_22/R603_22
Fast Recovery Rectifier
220 Amperes Average, 1600 Volts

Absolute Maximum Ratings

Characteristics	Symbol	R602_22/R603_22	Units
RMS Forward Current	$I_{F(rms)}$	345	Amperes
Average Forward Current	$I_{F(av)}$	220	Amperes
One-half Cycle Surge Current	I_{FSM}	3500	Amperes
3 Cycle Surge Current	I_{FSM}	2700	Amperes
10 Cycle Surge Current	I_{FSM}	2100	Amperes
I^2t (for Fusing), Times ≥ 8.3 milliseconds	I^2t	51000	A^2sec
Storage Temperature	T_{stg}	-40 to +190	$^{\circ}C$
Operating Temperature	T_j	-40 to +150	$^{\circ}C$
Mounting Torque (Lubricated)		360	in-lb

Electrical and Thermal Characteristics

Characteristics	Symbol	Test Conditions	R602_22/R603_22	Units
Current - Conducting State Maximums				
Forward Voltage Drop	V_{FM}	$T_j = 25^{\circ}C$, $I_{FM} = 800A$	2.75	Volts

Voltage - Blocking State Maximums

Repetitive Peak Reverse Voltage (Rated Limit)	V_{RRM}		1600	Volts
Non-rep. Trans. Peak Rev. Voltage (Rated Limit)	V_{RSM}	$t \leq 5.0msec$	1800	Volts
Reverse Leakage Current, mA peak	I_{RRM}	T_j at max., $V_{RRM} = \text{Rated}$	50	mA


Switching

Maximum Reverse Recovery Time	t_{rr}	$I_{FM} = 785A$, $t_p = 100\mu sec$, $di_R/dt = 25A/\mu sec$, $T_C = 25^{\circ}C$	500	nsec
Maximum Reverse Recovery Time	t_{rr}	$I_{FM} = 785A$, $t_p = 100\mu sec$, $di_R/dt = 25A/\mu sec$, $T_C = 150^{\circ}C$	1.1	μsec

Thermal

Maximum Resistance, Junction to Case	$R_{\theta(j-c)}$	0.17	$^{\circ}C/Watt$
Maximum Resistance, Case to Sink (Lubricated)	$R_{\theta(c-s)}$	0.10	$^{\circ}C/Watt$

Reverse Recovery Wave Form



Transient Thermal Impedance Vs. Time

