



GAM
T1

NNO

- Screw type fuse carrier



- UL 4248-1 / UL 512
- CSA C22.2 no. 39
- NF C 93-436 - Modèle HB02
- Contrôle de Conformité de Qualité (CCQ)

- UL File Number: E41738
- CSA File Number: 23151

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [Approvals](#), [CE declaration of conformity](#), [RoHS](#), [CHINA-RoHS](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

Fuse-Link	6.3 x 32mm
Mounting	Panel Mount, Rear Side
Mounting	Fixing Nut
Terminal	Solder
Rated Voltage	250 VAC
Rated current	10A (NF), 10A (UL/CSA)
Rated Power Acceptance IEC	2.5W / 10A @ Ta 23°C Admissible power acceptance at higher ambient temperature see derating curves
Degree of Protection	IP 40 / IP 67
Protection Class	Suitable for appliances with protection class I or II acc. to IEC 61140
Admissible Ambient Air Temp.	-40°C to 85°C
Climatic Category	40/085/21 acc. to IEC 60068-1
Material: Socket	Thermoset, black
Unit Weight (Socket/Cap)	19 g
Storage Conditions	0°C to 60°C, max. 70% r.h.
Product Marking	Type, Dielectric strength, Current, Approvals, HB2

Soldering Methods	Iron
Resistance to Vibration	acc. to NF C 20-706 / IEC 60068-2-6 test Fc
Shocks	acc. to NF C 20-706 / IEC 60068-2-27
Bumps	acc. to NF C 20-729 / IEC 60068-2-29
Salt Mist	acc. to NF C 20-711 / IEC 60068-2-11
Dump Heat	acc. to NF C 20-604
Climatic Composite	acc. to NF C 20-619 Phases D and F
Admissible Torque on Fixing Nut	max 1.2Nm
Panel Thickness s	max 5mm



Mounting holes

Variants

Holder	Cap	Fuse-Link	Degree of Protection					NNO	Reference	Order Number
●	Fingergrip	6.3 x 32mm	IP 40	●	●	●	●	●	23312P	7092.2520
●	Fingergrip	6.3 x 32mm	IP 67						23312ERJJP	7092.2630

Packaging Unit
 Bulk (100 pcs.)