

DC Connector, Socket, 6.3 mm, 2.35 mm, 2-pole, solder terminal

**Description**

- Solder terminal:
Screw-on mounting, from rear-side
- Low Voltage DC Plug and Socket
- DC Plug: 2-pole, straight



Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)

Technical Data

Diameter	6.3 mm / 2.35 mm
Number of Poles	2-pole
Ratings DC	1 A / 12 VDC
Dielectric Strength	500 VDC
Insulation Resistance	> 100 MΩ @ 500 VDC

Allowable Operation Temp.	-20 °C to 70 °C
Terminal	solder terminal silver plated
Mounting	Screw-on mounting wall thickness max. 5.5 mm
Style	straight
Lifetime	5000 Insertions

Dimensions**Diagrams****Variants**

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
DC Plug/Socket	6.3	2-pole	solder terminal	4840.2210

Packaging unit 250 Pcs

Mating Inlets/Plugs

Category / Description



[DC Plug/Socket Overview complete](#)

DC Connector, Plug, 5.5x2.5 mm, 2-pole, solder terminal	4840.1210
DC Connector, Plug, 5.5x2.5 mm, 2-pole, straight, with cable	4840.5210
DC Connector, Plug, 5.5x2.5 mm, 2-pole, angled, with cable	4840.5211

[DC Plug/Socket further types to 4840 DC-Stecker, verschiedene](#)