

DC Connector, Socket, 6.0 mm, 2-pole, solder terminals for PCB



Description

- PCB Mounting:
Drop-in type, from rear-side
- Low Voltage DC Plug and Socket
- DC Plug: 2-pole, straight

Weblinks


[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)

Technical Data


Diameter	6.0 mm / 3.0 mm / 1.05 mm
Number of Poles	2-pole
Ratings DC	2 A / 13.5VDC
Dielectric Strength	500VDC
Insulation Resistance	> 100 MΩ @ 500VDC

Allowable Operation Temp.	-20 °C to 70 °C
Terminal	PCB terminals silver plated
Mounting	Drop-in type
Style	straight
Lifetime	5000 Insertions

Dimensions



Diagrams



Variants

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
DC Plug/Socket	6.0	2-pole	PCB terminals	4840.2221

Packaging unit 500 Pcs

Mating Inlets/Plugs

Category / Description

[DC Plug/Socket Overview complete](#)



DC Connector, Plug, 5.5x3.3 mm, 2-pole, solder terminal	4840.1220
DC Connector, Plug, 5.5x3.3 mm, 2-pole, straight, with cable	4840.5220
DC Connector, Plug, 5.5x3.3 mm, 2-pole, angled, with cable	4840.5221

[DC Plug/Socket further types to 4840 DC-Stecker, verschiedene](#)