

DIN Connector, Plug, 3-pole, solder terminal



3-pole

**Description**

- Solder terminal:
for cable mounting
- DIN Plug: 3-pole, straight


Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)



Technical Data

Diameter	9.0 mm
Number of Poles	3-pole
Ratings DC	2 A / 12 VDC
Ratings AC	1 A / 100 VAC
Dielectric Strength	250 VAC
Insulation Resistance	> 50 MΩ @ 250 VDC

Allowable Operation Temp.	-20 °C to 70 °C
Terminal	solder terminal silver plated
Lifetime	5000 Insertions

Dimensions

Cable diameter max. 5.0 mm

**Variants**

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
DIN Plug/Socket	9.0	3-pole	solder terminal	4850.1310

Packaging unit 100 Pcs**Mating Outlets/Connectors**

Category / Description

[DIN Plug/Socket Overview complete](#)

DIN Connector, Socket, 3-pole, solder terminals for PCB	4850.2300
DIN Connector, Socket, 3-pole, solder terminals for PCB	4850.2310
DIN Connector, Inline Socket, 3-pole, solder terminal	4850.3300

[DIN Plug/Socket further types to 4850 DIN-Stecker, verschiedene](#)