

DIN Connector, Plug, 5-pole, solder terminal

**Description**

- Solder terminal:
for cable mounting
- DIN Plug: 5-pole, straight


Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)

Technical Data

Diameter	9.0 mm
Number of Poles	5-pole
Ratings DC	2 A / 12 VDC
Ratings AC	1 A / 100 VAC
Dielectric Strength	250 VAC
Insulation Resistance	> 50 MΩ @ 250 VDC

Allowable Operation Temp.	-20 °C to 70 °C
Terminal	solder terminal silver plated
Lifetime	5000 Insertions

Dimensions**Variants**

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
DIN Plug/Socket	9.0	5-pole	solder terminal	4850.1510

Packaging unit 100 Pcs

Mating Outlets/Connectors**Category / Description**

[DIN Plug/Socket Overview complete](#)

DIN Connector, Socket, 5-pole, solder terminals for PCB	4850.2500
DIN Connector, Socket, 5-pole, solder terminals for PCB	4850.2510
DIN Connector, Inline Socket, 5-pole, solder terminal	4850.3500

[DIN Plug/Socket further types to 4850 DIN-Stecker, verschiedene](#)