

DIN Connector, Socket, 8-pole, solder terminals for PCB

**Description**

- PCB Mounting
- DIN Plug: 8-pole, straight


Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)

Technical Data

Diameter	9.0 mm
Number of Poles	8-pole
Ratings DC	1 A / 12 VDC
Ratings AC	1 A / 100 VAC
Dielectric Strength	250 VAC
Insulation Resistance	> 50 MΩ @ 250 VDC

Allowable Operation Temp.	-20 °C to 70 °C
Terminal	PCB terminals silver plated
Lifetime	5000 Insertions

Dimensions**Variants**

Product group	Diameter [mm]	Number of Poles	Terminal	Order Number
DIN Plug/Socket	9.0	8-pole	PCB terminals	4850.2810

Packaging unit 750 Pcs

Mating Inlets/Plugs

Category / Description



DIN Plug/Socket Overview complete

DIN Connector, Plug, 8-pole, solder terminal

4850.1810

DIN Plug/Socket further types to 4850 DIN-Stecker, verschiedene

