

Clip, 6.3x32 mm, 32 A, BeCu



600 VAC/DC · 32 A (UL)

**Description**

- BeCu Clip up to 32 A Application

Standards

- UL 4248-1 / UL E 39328
 - CSA 22.2 no. 4248.1

Applications

- Industrial electronic
 - Photovoltaic

References

Fuseholder to SUT 6.3x32



Weblinks

pdf-datasheet, html-datasheet, General Product Information, Approvals, CE declaration of conformity, RoHS, CHINA-RoHS, e-Shop, SCHURTER-Stock-Check, Distributor-Stock-Check, Detailed request for product

Technical Data

Fuse-Link	6.3 x 32 mm
Mounting	PCB
Terminal	Solder THT
Rated Voltage	600 VAC/DC
Rated current	32 A (UL)
Admissible Ambient Air Temp.	-55 °C to 125 °C
Material: Terminals	BeCu
Storage Conditions	0 °C to 60 °C, max. 70% r.h.

Soldering Methods	Wave
Solderability	235 °C / 2 sec acc. to IEC 60068-2-20, Test Ta, method 1
Resistance to Soldering Heat	260 °C / 10 sec acc. to IEC 60068-2-20, Test Tb, method 1A

Dimensions


Drilling diagram

Variants

Clip	Material: Terminals	Order Number
•	Tin-plated Beryllium-Copper	8040.0001
•	Silver-plated Beryllium-Copper	8040.0003

Packaging Unit

Bulk (1000 pcs.)