

Miniature Fuse, 5 x 20 mm, Super-Time-Lag TT, NF, 220 VAC



NF C 93-435 · 220 VAC · Super-Time-Lag TT



Description

- Low Breaking Capacity

Standards

- UL 248-14
- NF C 93-435 - Model HA20
- Contrôle de Conformité de Qualité (CCQ)

Approvals

- UL File Number: E42088

Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [Approvals](#), [CE declaration of conformity](#), [RoHS](#), [CHINA-RoHS](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

Technical Data


Rated Voltage	32 - 220 VAC
Rated current	0.031 - 15 A
Breaking Capacity	40 A - 100 A
Characteristic	Super-Time-Lag TT
Mounting	Fuseholder / Clip
Admissible Ambient Air Temp.	-40 °C to 70 °C
Climatic Category	40/070/56 acc. to IEC 60068-1
Material: Tube	Glass
Material: Endcaps	Nickel-Plated Copper Alloy
Unit Weight	1.4 g
Storage Conditions	0 °C to 60 °C, max. 70% r.h.
Product Marking	Type, HA20, Current, Characteristic

Resistance to Vibration acc. to NF C 20-706 / IEC 60068-2-6, test Fc

Shocks acc. to NF C 20-706 / IEC 60068-2-27

Salt Mist acc. to NF C 20-711 / IEC 60068-2-11

Dimensions



Pre-Arcing Time

Rated Current In	1.1 x In min.	2.0 x In max.	2.1 x In max.	3.0 x In min.	3.0 x In max.	5.0 x In min.	5.0 x In max.	10.0 x In min.
0.031 A - 1.25 A	-	10 min	-	1 s	60 s	300 ms	10 s	30 ms
1.6 A - 15 A	-	-	10 min	1 s	60 s	300 ms	10 s	30 ms

Variants

Rated Current [A]	Rated Voltage [VAC]	Breaking Capacity	Voltage Drop 1.0 I _n typ. [mV]	Power Dissipation 1.1 I _n typ. [mW]	Melting I ² t 10.0 Intyp. [A ² s]	 	GAM T1	NNO	Order Number
0.031	220	1)	3850	145	0.079	●		●	7030.3110
0.04	220	1)	3150	155	0.2	●		●	7030.3120
0.05	220	1)	2600	160	0.22	●	●	●	7030.3130
0.063	220	1)	2000	155	0.35	●	●	●	7030.3140
0.08	220	1)	1850	180	0.26	●	●	●	7030.3150
0.1	220	1)	1600	190	0.028	●	●	●	7030.3210
0.125	220	1)	2000	300	0.61	●	●	●	7030.3220
0.16	220	1)	745	150	0.2	●	●	●	7030.3230
0.2	220	1)	715	180	0.39	●	●	●	7030.3240
0.25	220	1)	480	150	0.4	●	●	●	7030.3250
0.31	220	1)	870	340	0.21	●	●	●	7030.3260
0.4	220	1)	665	340	0.64	●	●	●	7030.3270
0.5	220	1)	555	360	1	●	●	●	7030.3280
0.63	220	1)	460	370	1.6	●	●	●	7030.3290
0.8	220	1)	365	370	4.2	●	●	●	7030.3310
1	220	1)	295	365	9	●	●	●	7030.3320
1.25	220	1)	300	465	7.1	●	●	●	7030.3330
1.6	125	2)	280	535	22	●	●	●	7040.3110
2	125	2)	245	595	43	●	●	●	7040.3120
2.5	125	2)	210	630	128	●	●	●	7040.3130
4	125	3)	165	790	260	●	●	●	7040.3150
5	125	3)	175	1100	440	●	●	●	7040.3160
6.3	125	3)	105	775	800	●	●	●	7040.3170
8	125	4)	105	1000	1400	●			7040.3180
10	125	4)	90	1050	2200	●			7040.3190
12.5	32	5)	55	795	890				7040.3200

1) NF: 60 A @ 220 VAC , p.f. = 1.0

1) UL: 4000 A @ 125 VAC , p.f. ≥ 0.9 / 4000 A @ 125 VDC , L/R = 5 ms

2) NF: 40 A @ 125 VAC , p.f. = 0.7 - 0.8

2) UL: 100 A @ 125 VAC , p.f. ≥ 0.9

3) NF: 40 A @ 125 VAC , p.f. = 0.7 - 0.8

3) UL: 50 A @ 125 VAC , p.f. ≥ 0.9

4) UL: 50 @ 125 VAC , p.f. ≥ 0.9

5) 100 A @ 32 VAC , p.f. ≥ 0.9

Packaging Unit

Small Box Pack (10 pcs.)

Time-Current-Curves

