

Surface Mount Fuse, 1.05 x 0.55 mm, Super-Quick-Acting FF, 32 VDC



UL 248-14 · 32 VDC · Super-Quick-Acting FF

**Description**

- UL characteristic
- Low melting I²t-values, fast interruption

Standards

- UL 248-14
- CSA C22.2 no. 248.14

Approvals

- UL File Number: E41599

Applications

- Secondary Protection
- Circuits without inrush
- Semiconductor protection
- Digital Consumer Electronics

References
[Packaging Details](#)
Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [Approvals](#), [CE declaration of conformity](#), [RoHS](#), [CHINA-RoHS](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [Detailed request for product](#)



Technical Data

Rated Voltage	24 - 32 VDC
Rated current	0.375 - 5 A
Breaking Capacity	35 A
Characteristic	Super-Quick-Acting FF
Mounting	PCB, SMT
Admissible Ambient Air Temp.	-55 °C to 125 °C
Climatic Category	55/125/21 acc. to IEC 60068-1
Material: Housing	Thermoset
Material: Terminals	Gold-Plated Copper Alloy
Unit Weight	0.004 g
Storage Conditions	0 °C to 60 °C, max. 70% r.h.
Product Marking	Letter (see variants)

Soldering Methods	Reflow
Solderability	245 °C / 3 sec acc. to IEC 60068-2-58, Test Td
Resistance to Soldering Heat	260 +0/-5 °C / 30 sec acc. to IPC/JEDEC J-STD-020D, 1 cycle
Flammability	min. UL 94V-1 (acc. to EIA/IS-722, Test 4.12)

Dimensions

H 1.05 mm



Soldering pads

Pre-Arcing Time

Rated Current I _n	1.0 x I _n min	2.0 x I _n max
------------------------------	--------------------------	--------------------------

0.375 A - 5 A	4 h	5 s
---------------	-----	-----

Variants

Rated Current [A]	Rated Voltage [VDC]	Marking	Breaking Capacity	Voltage Drop 1.0 In max. [mV]	Voltage Drop 1.0 In typ. [mV]	Cold Resistance typ. [mΩ]	Melting I ² t 8.0 In typ. [A ² s]	 Order Number
0.375	32	E	1)	90	70	173	0.003	● 3414.0112.xx
0.5	32	F	1)	90	67	124	0.004	● 3414.0113.xx
0.75	32	G	1)	90	63	78	0.009	● 3414.0114.xx
1	32	H	1)	90	63	57	0.016	● 3414.0115.xx
1.5	32	K	1)	90	62	37	0.029	● 3414.0117.xx
2	32	N	1)	90	58	26	0.044	● 3414.0119.xx
2.5	32	O	1)	90	59	21	0.06	● 3414.0120.xx
3	32	P	1)	90	52	17	0.098	● 3414.0121.xx
4	32	S	1)	90	60	13	0.113	● 3414.0123.xx
5	24	T	2)	90	52	10	0.288	● 3414.0124.xx

Most Popular. Availability for all products can be searched real-time: <http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

1) 35 A @ 32 VDC

2) 35 A @ 24 VDC

Packaging Unit

.xx = .11 Blister Tape (100 pcs.)
 .xx = .22 Blister Tape 18 cm Reel (1000 pcs.)
 .xx = .24 Blister Tape 18 cm Reel (5000 pcs.)
 .xx = .26 Blister Tape 33 cm Reel (15000 pcs.)

Time-Current-Curves

