


REV	DOCUMENT	CHANGED BY	CHECK
B	0039823	KVS 15MAY08	ASD



CHARACTERISTICS		ELECTRICAL DATA		DESIGN UNITS: MM TOLERANCES UNLESS NOTED:		DRAWN	KSR	03DEC07	Honeywell					
OPERATING FORCE: 32gf MAX. DIFFERENTIAL FORCE: RELEASE FORCE: 8gf MIN. FREE POSITION: OPERATING POSITION: 15.3±4.5MM. PRE-TRAVEL: 12.0MM MAX. DIFFERENTIAL TRAVEL: 3.5MM MAX. OVER-TRAVEL: 5.3MM MIN. FULL OVERTRAVEL FORCE:		CONTACT ARRANGEMENT S.P.N.O				CHECK	RJ	03DEC07						
		17 CQC 16(4)A 250V~ 25T150 μ 5E4 RJ cRJ 16A 1/2HP 125/250VAC		NO PLACE X ± - ONE PLACE .X ± - TWO PLACE .XX ± 0.40 THREE PLACE .XXX ± - ANGLES X ± 2°		THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.			TITLE SWITCH - BASIC					
		THIRD ANGLE PROJECTION 		INTERPRET PER ASME Y14.5M-1994 OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY										
						AutoCAD			SIZE B	TYPE I	CAGE CODE	DRAWING NAME V15H16-CP200B03-K		REV B
									SCALE	—			SHEET	1 OF 1