


REV	DOCUMENT	CHANGED BY	CHECK
B	0039823	KVS 15MAY08	ASD



CHARACTERISTICS		ELECTRICAL DATA		DESIGN UNITS: MM				DRAWN		KSR		03DEC07		Honeywell					
CONTACT ARRANGEMENT S.P.D.T		16(4)A 250V~ 25T150 μ 5E4  16A 1/2HP 125/250VAC		TOLERANCES UNLESS NOTED:				CHECK		RJ		03DEC07							
OPERATING FORCE: 125gf MAX. DIFFERENTIAL FORCE: RELEASE FORCE: 30gf MIN. FREE POSITION: OPERATING POSITION: 15.3±2.5MM. PRE-TRAVEL: 6.0MM MAX. DIFFERENTIAL TRAVEL: 1.65MM MAX. OVER-TRAVEL: 2.2MM MIN. FULL OVERTRAVEL FORCE:				NO PLACE X ± ± ONE PLACE .X ± ± TWO PLACE .XX ± ± 0.40 THREE PLACE .XXX ± ± ANGLES X ± ± 2°				THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.				INTERPRET PER ASME Y14.5M-1994 OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY							
				THIRD ANGLE PROJECTION 				AutoCAD				SCALE		—		SHEET		1 OF 1	