


REV	DOCUMENT	CHANGED BY	CHECK
B	0039823	KVS 15MAY08	ASD



A

- 100

CHARACTERISTICS		ELECTRICAL DATA		DESIGN UNITS: MM		DRAWN	KSR	03DEC07	Honeywell						
CONTACT ARRANGEMENT S.P.D.T				TOLERANCES UNLESS NOTED:		CHECK	RJ	03DEC07							
OPERATING FORCE: 30gf MAX.		 22(8)A 250V~ 25T150 μ  22A 1HP 125/250VAC		NO PLACE X ± -		THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL. INTERPRET PER ASME Y14.5M-1994 OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY			TITLE SWITCH - BASIC						
DIFFERENTIAL FORCE: _____				ONE PLACE .X ± -											
RELEASE FORCE: 5gf MIN.				TWO PLACE .XX ± 0.40					SIZE B	TYPE E	CAGE CODE	DRAWING NAME V15H22-CZ100A03-K		REV B	
FREE POSITION: _____				THREE PLACE .XXX ± -					SCALE	—			SHEET	1	OF 1
OPERATING POSITION: 15.3±3MM.				ANGLES X ± 2°					THIRD ANGLE PROJECTION 						
PRE-TRAVEL: 6.4MM MAX.						AutoCAD									
DIFFERENTIAL TRAVEL: 2.4MM MAX.															
OVER-TRAVEL: 2.6MM MIN.															
FULL OVERTRAVEL FORCE: _____															