

MICRO SWITCH
a Honeywell Division

FED. MFG. CODE 91929

SWITCH - BASIC

CATALOG LISTING

V7-5F27D8-000-2

CW-C5036

CATALOG LISTING
V7-5F27D8-000-2
PAGE 1 OF 1

REPLACES

RELEASE NO PR-21371

M

ISSUE
2

CHECK

REVISIONS

A REL PR21371
DCS
25 OCT 94

CHECK

CHECK

DRAWN

DCS

17 JUN 94

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION



CHARACTERISTICS	ELECTRICAL DATA		SCALE FULL	DO NOT SCALE PRINT
OPERATING FORCE — — — 8-18 GRAMS	CONTACT ARRANGEMENT		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE ONE PLACE (.0) ±.030 TWO PLACE (.00) ±.015 THREE PLACE (.000) ±.005 ANGLES ± WEIGHT	
DIFFERENTIAL TRAVEL — — — .002-.010	S P N O			
OVERTRAVEL — — — — .050 MIN	L163	3A 125, <u>250</u> , 277 VAC 1/10HP <u>250</u> VAC		
RELEASE TRAVEL — — — — .010 MIN				
FREE POSITION — — — — .625 MAX				
		 		

