

CATALOG LISTING

V7-6C27D8-048

PAGE 1 OF 1

RELEASE NO PR-21263

REPLACES X98790-V7

M

ISSUE

5

REVIEWS

A	REL PR21263	DCS	29 JUL 94
B	CO 80192	DCS	16 OCT 95
C	CO 81480	DCS	22 JAN 96
D	0041196	JA	01JUU08

CHECK

01JUL08

ASD

CHECK

10 AUG 94

DCS

CHECK

15 JUL 94

DCS

DRAWN

RASTER

Honeywell FED.MFG.CODE 91929	SWITCH — BASIC	CATALOG LISTING V7-6C27D8-048 CW-C6034
--	--	--

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF HONEYWELL.

THIRD ANGLE PROJECTION

CHARACTERISTICS	ELECTRICAL DATA	SCALE FULL	DO NOT SCALE PRINT
OPERATING FORCE ———120 GRAMS MAX RELEASE FORCE ———19 GRAMS MIN DIFFERENTIAL TRAVEL ———.010—.054 OVERTRAVEL ———.124 MIN RELEASE TRAVEL ———.030 MIN	CONTACT ARRANGEMENT S P N O L215 15.1A 1/2HP 125, 250 OR 277 VAC 1/2A 125 VDC 1/4A 250 VDC; 5A 125 VAC "L"	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE ONE PLACE (.0) ±.030 TWO PLACE (.00) ±.015 THREE PLACE (.000) ±.005 ANGLES ±	
		WEIGHT	