

**MICRO SWITCH**  
a Honeywell Division

FED. MFG. CODE 91929

# SWITCH-BASIC

CATALOG LISTING

**V7-7A19D8**

**CW-C6076**

CATALOG LISTING

**V7-7A19D8**

PAGE 1 OF 1

REPLACES X99905-V7

RELEASE NO. PR-21744

REVISIONS

| REV | DATE    | BY  | CHKD    | DESCRIPTION |
|-----|---------|-----|---------|-------------|
| A   | 0085964 | SBH | 30JAN12 |             |

ISSUE

**2**

CHECK

30JAN12

CHECK

CMH

DCS

21 JUN 95

CHECK

30JAN12

CHECK

CMH

RASTER

DRAWN

ANSI Y14.5M-1982 APPLIES

THIRD ANGLE PROJECTION

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

SCALE NONE DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

CHARACTERISTICS

OPERATING FORCE — — — — 8 OZ MAX

RELEASE FORCE — — — — 2 OZ MIN

DIFFERENTIAL TRAVEL — .002 — .015

OVERTRAVEL — — — — .050 MIN

FREE POSITION — — — — .625 MAX

RELEASE TRAVEL — — — — .010 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT

S P D T

L162 5A 125; 250 277 VAC

1/10 HP 250 VAC

ONE PLACE ( .0 ) ±.030

TWO PLACE ( .00 ) ±.015

THREE PLACE ( .000 ) ±.005

ANGLES ±

WEIGHT

PLASTIC PLUNGER

ANSI Y14.5M-1982 APPLIES