

**MICRO SWITCH**FREEPORT, ILLINOIS, U.S.A.
A DIVISION OF HONEYWELL

FED. MFG. CODE 91929

SWITCH-BASIC

CATALOG LISTING

WA-2R96-P51**WA-2R96-P51**

PAGE 1 OF 1

MDRAWING
NUMBER**9**

ISSUE

REPLACES

RELEASE NO.

CHECK

64

11 SEP 64

11 SEP 64

RFS

11 SEP 64

CHECK

64

11 SEP 64

LSD

CHECK

64


11 SEP 64

LSD

CHECK

64

11 SEP 64

**NOTES**

▲ MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF
.139 MAX DIA ON 1.000±.002 CENTERS

2-PLASTIC MATERIAL USED:

CASE----DUREZ 16274 OR EQUIVALENT (NORMALIZED)

COVER----GE12983 OR EQUIVALENT (NORMALIZED)

PLUNGER---GE EF-4530 OR EQUIVALENT

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF MINNEAPOLIS-HONEYWELL REGULATOR CO. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

CHARACTERISTICS

OPERATING FORCE - - - 14-22 OZ

RELEASE FORCE - - - - 10 OZ MIN

DIFFERENTIAL TRAVEL - -.0020- .0075

OVERTRAVEL - - - - - .010 MIN

ELECTRICAL DATA**CONTACT ARRANGEMENT**
S P N C

UNDERWRITERS' LAB. INC. LISTED RATING
-L23- 20 A-125, 250, OR 480 VAC
10 A-125 VAC "L"
1 HP-125 VAC ; 2 HP-250 VAC
1/2 A-125 VDC ; 1/4 A-250 VDC

-L288-
-L299-
-L308-



20(3)A 250V ~ T85 5E4

SCALE FULL

DO NOT SCALE PRINT

UNLESS OTHERWISE
NOTED

DIMENSIONS ARE IN INCHES

TOLERANCES ARE:

ONE PLACE (.0) ±.030
TWO PLACE (.00) ±.015
THREE PLACE (.000) ±.005
ANGLES 1/2°

WEIGHT .063 LB

RASTER

FO-50378

DRAWN

M B F

10 SEP 64