

REVISIONS	CO- 95009		S A V 14 MAY 99		BS 04DEC07	
A			B		0035412	

CHECK		ASD	

14 MAY 99				

CHECK		JAF	

PTC/CAD	2D	DRAWN	S A V	14MAY99
---------	----	-------	-------	---------

PTC / CAD 20

S	A	V	I 4 MAY 99
---	---	---	------------

```

OPERATING FORCE-----11 - 17 OZ
DIFFERENTIAL FORCE-----1 - 5 OZ
RELEASE FORCE
PRETRAVEL
DIFFERENTIAL TRAVEL-----.0001 - .0011
OVERTRAVEL-----.005 MIN
FREE POSITION

```

CHARACTERISTICS

ELECTRICAL DATA

CONTACT ARRANGEMENT

S P N C

L82 22A 125, 250 OR 277 VAC
1/4HP 125 VAC, 1/2HP 250 VAC

L288
L315
L318

  

22A 250V ~ T85 5E4

SCALE	FULL	DO NOT SCALE PRINT
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		
ONE PLACE	(.0)	± .030
TWO PLACE	(.00)	± .015
THREE PLACE	(.000)	± .005
ANGLES		±
WEIGHT	.060 LB	

ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

NOTE

MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF Ø .139 MAX ON 1.000±.002 CENTERS

