

MICRO SWITCHFREEPORT ILLINOIS, U.S.A
A DIVISION OF HONEYWELL INC.
FED. MFG. CODE 91929**SWITCH-BASIC**

CATALOG LISTING

WZ-3RW8221555514T-S

WZ-3RW8221555514T-S

PAGE 1 OF 1

REPLACES

RELEASE NO. PR-17934

MDRAWING
NUMBER

6

ISSUE

CHECK

REVISIONS

A	CO67209
J A P	
2 MAY 90	
B	CO-69351-D
JWB	
18 JUL 91	
C	CO-77591
DAW	
22 JUN 94	
D	CO-79125
SAD	
30 NOV 94	
E	CO93346
DLT	
17 AUG 98	

CHECK

JAN 90

JAP


CHECK

JAN 90

FORMTEK

FO-52848-B


DRAWN

**NOTE**

1 - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .139 MAX DIA ON $1.000 \pm .002$ CENTERS

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

**CHARACTERISTICS**

OPERATING FORCE — — 10 OZ MAX
RELEASE FORCE — — 1 1/2 OZ MIN
DIFFERENTIAL TRAVEL — .007—.030
OVERTRAVEL — — — .094 MIN

ELECTRICAL DATA

CONTACT ARRANGEMENT
S P N C

L9

10A 125, 250 OR 480 VAC
1/2 A 125 VDC, 1/4 A 250 VDC

L288

**SCALE FULL****DO NOT
SCALE PRINT**

UNLESS OTHERWISE SPECIFIED
TOLERANCES ARE

ONE PLACE (.0) $\pm .030$
TWO PLACE (.00) $\pm .015$
THREE PLACE (.000) $\pm .005$
ANGLES $\pm$

WEIGHT